

INTERNET PHONE USING A USB INTERFACE TO TRANSMIT SIGNALS

BACKGROUND OF THE INVENTION

Field of Invention

5 The present invention relates to an Internet phone and, in particular, to an Internet phone that transmits signals through a USB interface.

Related Art

10 The development of thin clients (including windows terminals, network terminals) has been turning to extremely thin clients in order to follow the trend in light, thin, and miniaturized electronic products. This provides superiority in reducing costs so as to have a competitive power in the thin client market.

15 The usual voice over Internet phone (VOIP) refers to the software, hardware and technologies in transmitting digital data through the IP packages on the Internet. Its main objective is to make long distance phone calls cheaper. However, both the VOIP structure and cost are extremely complicated and expensive. If a thin client with the online function can be utilized to provide the Internet phone function, the thin client will have more extra values in applications.

SUMMARY OF THE INVENTION

20 It is a primary objective of the invention to add extra functions to thin clients with the online function and a digital phone connected through a USB interface so as to provide the online and telephone functions.

The Internet phone transmitting data through a USB interface includes a voice message sending procedure and a voice message receiving procedure.

First, the voice message sending procedure receives outgoing message signals through a

Internet service provider (ISP) 30. The thin client 10 has a USB interface port 50 for coupling to a digital phone 60. The digital phone 60 also has a USB interface port 52.

5 The digital phone 60 further has a transceiver, buttons, and a display. The LAN 20 connecting the thin client 10 and the ISP 30 can be a cable modem or an asymmetric digital subscriber line (ADSL) modem. Through the Ethernet network protocol, the above-mentioned thin client 10 is then equipped with the online function.

10 With reference to FIG. 2, outgoing message signals are entered through a digital phone 60 (step 210). The outgoing message signals are then transmitted to a host through a USB interface 50, 52 (step 220). The host can be a thin client 10 or an online machine which converts the outgoing message signals into outgoing message VOIP package (step 230). Finally, the outgoing message VOIP package is stored in an LAN 20 and then transmitted to a target through the Internet 40 (step 240).

15 With reference to FIG. 3, an incoming message VOIP package is transmitted from the target back to the LAN 20 through the Internet 40 (step 310). The host then converts the incoming message VOIP package into incoming message signals (step 320). The host further transmits the incoming message signals to the digital phone 50 through the USB interface 50, 52 (step 330). Finally, the incoming message signals are output through the digital phone (step 340).

20 The invention is featured in a digital phone 50 with a USB data transmission interface and utilizes the existing online function of a thin client 10 to connect the thin client 10 and the digital phone 50 through a USB interface, so that the combination has the function of a telephone in addition to that of a thin client 10.

25 The invention being thus described, it will be obvious that the same may be varied in many ways. Such variations are not to be regarded as a departure from the spirit and scope of the invention, and all such modifications as would be obvious to one skilled in the art are intended to be included within the scope of the following claims.